



NI6F-360A



FEATURES

- **HD 3072 x 2048 @ 25fps**
- 6 Megapixel High Resolution
- 1/1.8" Progressive Scan CMOS
- 1.27mm Fisheye Lens, 360° Panoramic View
- IR Distance up to 30ft / 9m
- Color: 0.05 Lux @ F1.2 (AGC ON); B/W: 0.3 Lux @ F2.8 (AGC ON), 0 Lux w/ IR
- Multiple ePTZ streams with preset and patrol functions
- Mechanical IR Cut Filter (ICR)
- 3D DNR, Digital WDR
- Built-in Micro SD / SDHC / SDXC Card Slot, Supports Up to 128G
- Audio / Alarm Input & Output
- Max. 11W
- 12V DC \pm 10% / PoE
- IP66 / IK10 Rating


SPECIFICATIONS - Product Code: NI6F-360A

PIC: IP-17-6

Image Sensor	1/1.8" Progressive Scan CMOS
Max. Image Resolution	3072 x 2048
Frame Rate	High-frame Mode: support; Multi-channel Mode: Support 50Hz: 1 x fisheye (3072 x 2048, 25fps) or (2048 x 2048, 25fps) or 4 x PTZ at (1024 x 768, 30fps); 60Hz: 1 x fisheye (3072 x 2048, 25fps) or (2048 x 2048, 30fps) or 4 x PTZ at (1024 x 768, 30fps) 50Hz: 1 x fisheye (1280 x 1280, 12.5fps) and 1 x panoramic (2048 x 1536, 12.5fps) and 3 x PTZ (1024 x 768, 12.5fps) 60Hz: 1 x fisheye (1280 x 1280, 15fps) and 1 x panoramic (2048 x 1536, 15fps) and 3 x PTZ (1024 x 768, 15fps)
Number of Streams	High Frame Rate Mode: 1 or 4; Multi-Channel: up to 5 (No sub-streams)
Shutter Speed	1/25 (1/30)s ~ 1/100,000s
Minimum Illumination	0.05 Lux @ (F1.2, AGC ON), 0.3 Lux @ (F2.8, AGC ON), 0 Lux with IR
Day & Night	Electronic IR Cut Filter (ICR)
Lens	1.27mm @F2.8, Angle of View: 360°
Lens Mount	M12
IR Distance	30ft / 9m
Digital Noise Reduction	3D DNR
Wide Dynamic Range	Digital WDR
Image Settings	Saturation, Brightness, Contrast, Hue, Sharpness, AGC, White Balance
High Light Compensation	Supports
Day / Night Switch	Auto / Manual / Scheduled / Alarm Trigger
Video Compression	H.264 / MJPEG
Audio Compression	G.711 / G.722.1 / G.726 / MP2L2
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
H.264 Type	Baseline Profile / Main Profile / High Profile
Video Bit Rate	32Kbps ~ 16Mbps
Alarm Trigger	Motion Detection, Dynamic Analysis, Tamper Alarm, Network Disconnect, IP Address Conflict, Storage Full, Storage Error
Security	User Authentication, Watermark, IP Address Filtering, Anonymous Access
Network Storage	NAS, SAMB / CIFS
On-Board Storage	Built-in Micro SD/SDXC Card Slot, up to 128 GB
Standard	ONVIF, PSIA, CGI
Communication Interface	1 RJ45 10M/100M/1000M Ethernet port; 1 RS-485 interface (-S)
Power Source	12V DC \pm 10% / PoE
Power Consumption	Max. 11W
Operating Temperature	-22°F ~ 140°F / -30°C ~ 60°C (Indoor Dome); Humidity: 95% or less (Non-Condensing)
Protection	IP66 / IK10
Dimension	6.46 x 6.02 x 1.72 inches / 164 x 152.8 x 43.8 mm
Net Weight	3.08 lbs / 1.4 kgs

*Specifications and appearance are subject to change without notice.

DIAGRAM



OPTIONAL ACCESSORIES



BK-115