

SS-NI12F-360A



12MP Fisheye Network Camera



- 1/1.7" Progressive Scan CMOS
- 12.4 MP effective sensor
- Up to 4000 × 3072 resolution
- BLC, AGC, ATW, WDR, Flickerless
- Line crossing and intrusion detection
- OSD 16 characters
- Up to 15m IR range
- 360° view angle
- Built-in microphone & speaker
- Audio/Alarm IO/ RS485(-S model)
- IP66(-V model)
- IK10 vandal proof(-V model)

Multiple Display Modes

The 12MP IR Fisheye Network Camera supports several viewing modes, including the 360° view, a horizontal panoramic view, PTZ quad view modes. Customers can also utilize this smooth PTZ function to easily pan, tilt and zoom, on any region of interest (ROI).

It is a great choice for detailed coverage of wide, open areas like airports, shopping malls, parking lots, retail stores, offices, restaurants, classrooms, and more.

NI12F-360A is designed to single-handedly capture images from every corner of a particular location and eliminate blind spots. It features a progressive scan CMOS sensor to provide high-resolution images of up to 4000 × 3072, and a fisheye lens for a 360 panoramic or multiple de-warped views. Furthermore, IR functionality provides up to 15m IR distance of visibility under low or even zero-light conditions.

12MP Fisheye Network Camera

Specification


Camera		
Image Sensor		1/1.7” Progressive Scan CMOS
Min. Illumination		0.01 Lux @ (F1.2, AGC ON), 0.04 Lux @ (F2.4, AGC ON), 0 Lux with IR
Shutter Speed		1/25(1/30)s ~ 1/100,000s
Lens		1.98mm @F2.4, angle of view: 360°
Lens Mount		M12
Day & Night		ICR
Compression Standard		
Video Compression		H.264 / MJPEG
H.264 Type		Baseline Profile / Main Profile / High Profile
Video Bit Rate		32 Kbps – 16 Mbps
Audio Compression(-S)		G.711/G.726/MP2L2
Audio Bit Rate		64Kbps(G.711) / 16Kbps(G.726) /64Kbps(MP2L2)
Image		
Max. Resolution		4000 × 3072
Live Mode	Mode1	1×Fisheye(main stream) + 1×Fisheye(sub stream) + 3×PTZ
	Mode2	1×Panorama(main stream) + 1×Panorama(sub stream)
	Mode3	4PTZ
	Mode4	Fisheye
Frame Rate	Mode1	50Hz: 1×Fisheye(2560×2560, 2048×2048, 1280×1280, 10fps) + 1×Fisheye(720×720, 10fps) +3×PTZ(1600×1200, 10fps) 60Hz: 1×Fisheye(2560×2560, 1280×1280, 10fps) + 1×Fisheye(720×720, 10fps) +3×PTZ(1600×1200, 10fps)
	Mode2	50Hz:1×Panorama(3072×2304, 3072×1152, 12.5fps) + 1×Panorama(704×576, 12fps) 60Hz:1×Panorama(3072×2304, 3072×1152, 15fps) + 1×Panorama(704×576, 15fps)
	Mode3	50Hz: 4×PTZ(1600×1200,12.5fps) 60Hz: 4×PTZ(1600×1200,15fps)
	Mode4	50Hz: 1×Fisheye(4000×3072, 20fps,3072×3072, 2560×2560, 25fps)+1×fisheye(720×720, 704×576, 12.5fps) 60Hz: 1×Fisheye(4000×3072, 20fps,3072×3072, 2560×2560, 25fps)+1×fisheye(720×720, 704×576, 15fps)
Digital Noise Reduction		3D DNR
Image Setting		Saturation, Brightness, Contrast, Hue, Sharpness, AGC, White Balance
Wide Dynamic Range		Digital WDR
Day/Night Switch		Auto/Schedule/Alarm Trigger
ROI		Up to 4 fixed areas in each stream
Intelligent		
Analytics		Heatmap (Recording the motion of foot traffic over a period of time and displays temporal density and spatial statistics in different colors), people counting
Network		
Network Storage		NAS (Support NFS,SMB/CIFS)

12MP Fisheye Network Camera

Alarm Trigger	Line crossing detection, Intrusion detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect, IP address conflict, Storage exception
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
Security	User Authentication, Watermark, IP address filtering, Anonymous access
Interface	
Communication Interface	1 RJ45 10M/100M/1000M Ethernet interface; 1 RS485 interface(-S)
Audio Input	1 3.5mm audio interface, Mic in/Line in (-S); 1 built-in microphone by default, 24db
Audio Output	1 3.5mm audio output interface (-S); 1 built-in speaker by default, support echo cancellation
Alarm Input(-S)	1
Alarm Output(-S)	1
On-board storage	Built-in Micro SD/SDHC/SDXC slot, up to 128 GB
General	
Operating Conditions	Indoor: -10 °C – 50 °C (14 °F – 122 °F) -V: -30 °C – 60 °C (-22 °F – 140 °F) Humidity 95% or less (non-condensing)
Power Supply	12 VDC ± 10% / PoE (802.3af)
Power Consumption	Max. 14.7W (up to 12W IR off)
IR Range	15 meters
Impact Protection	-V: IEC60068-2-75Eh, 20J; EN50102, up to IK10
Ingress Protection level	-V: IP66
Dimensions	164x152.8x43.8mm(6.46"x6.02"x1.72")
Weight	1400g

Dimensions

Accessories



Junction box



Inclined ceiling mount



Wall mount



Pendent mount

